

User manual

S27C390H

The color and the appearance may differ depending on the product, and the specifications are subject to change without prior notice to improve the performance.

| BEFORE USING THE | 7 7 | Copyright Icons used in this manual |
|----------------------|---------------|---|
| PRODUCT | 8 | Cleaning |
| | 9 | Securing the Installation Space |
| | 9 | |
| | | Precautions for storage |
| | 10 | Safety Precautions |
| | 10 11 | Symbols for safety precautions Electricity and Safety |
| | 12 | Installation and Safety |
| | 14 | Operation |
| | 18 | Correct posture to use the product |
| PREPARATIONS | 40 | |
| PREPARATIONS | 19 | Checking the Contents Removing the Packaging |
| | 20 | Checking the Components |
| | 21 | Parts |
| | 21 | Frontal Button |
| | 23 | Reverse Side |
| | 24 | Installation |
| | 24 | Attaching the Stand |
| | 25 | Removing the Stand |
| | 26 27 | Adjusting the Product Tilt Anti-theft Lock |
| | <u> </u> | ATTE THOIL LOOK |
| CONNECTING AND USING | 28 | Before Connecting |
| A SOURCE DEVICE | 28 | Pre-connection Checkpoints |

| | 29 29 30 30 31 32 33 34 | Connecting and Using a PC Connection Using the D-SUB Cable (Analog Type) Connection Using the HDMI Cable Connection Using an HDMI-DVI Cable Connecting the Power Driver Installation Setting Optimum Resolution Changing the Resolution Using a PC |
|--------------|--|--|
| SCREEN SETUP | 38 38 | Brightness Configuring Brightness |
| | 39 39 | Contrast Configuring Contrast |
| | 40 40 | Sharpness Configuring Sharpness |
| | 41 41 | SAMSUNG MAGIC Bright Configuring SAMSUNG MAGIC Bright |
| | 43 43 | SAMSUNG MAGIC Angle Configuring SAMSUNG MAGIC Angle |
| | 44 44 | SAMSUNG MAGIC Upscale Configuring SAMSUNG MAGIC Upscale |
| | 45 45 | Image Size Changing the Image Size |
| | 46 46 | HDMI Black Level Configuring the HDMI Black Level Settings |
| | 47 47 | H-Position & V-Position Configuring H-Position & V-Position |
| | 48 48 | Coarse Adjusting Coarse |
| | 49 | Fine Adjusting Fine |

| CONFIGURING TINT | 50 50 | Red Configuring Red |
|------------------|-----------------|--|
| | 51 51 | Green Configuring Green |
| | 52 52 | Blue Configuring Blue |
| | 53 53 | Color Tone Configuring the Color Tone Settings |
| | 54 54 | Gamma Configuring Gamma |
| COORDINATING OSD | 55 55 | Language Configuring Language |
| | 56 56 | Menu H-Position & Menu V-Position Configuring Menu H-Position & Menu V- Position |
| | 57 57 | Display Time Configuring Display Time |
| | 58 58 | Transparency Changing Transparency |
| SETUP AND RESET | 59 59 | Reset Initializing Settings (Reset) |
| | 60 | Eco Saving Configuring Eco Saving |
| | 61 61 | Off Timer Configuring Off Timer |
| | 62 62 | Turn Off After Configuring Turn Off After |
| | 63 | PC/AV Mode Configuring PC/AV Mode |

| | 64 64 | Key Repeat Time Configuring Key Repeat Time |
|-----------------------------|------------------------|---|
| | 65 65 | Source Detection Configuring Source Detection |
| | 66 66 | Customized Key Configuring Customized Key |
| INFORMATION MENU AND OTHERS | 67 67 68 | INFORMATION Displaying INFORMATION Configuring Brightness and Contrast in the Initial Screen |
| INSTALLING THE SOFTWARE | 69 69 69 70 | MagicTune What is "MagicTune"? Installing the Software Removing the Software |
| | 71 71 72 | MultiScreen Installing the Software Removing the Software |
| TROUBLESHOOTING GUIDE | 73 73 73 73 | Requirements Before Contacting Samsung Customer Service Center Testing the Product Checking the Resolution and Frequency Check the following. |
| | 76 | Q & A |
| SPECIFICATIONS | 78 80 | General PowerSaver |
| APPENDIX | 80 | Standard Signal Mode Table Contact SAMSUNG WORLD WIDE |

| 88 | Responsibility for the Pay Service (Cost to Customers) |
|----|--|
| 88 | Not a product defect |
| 88 | A Product damage caused by customer's fault |
| 89 | Others |
| 90 | Correct Disposal |
| 90 | Correct Disposal of This Product (Waste |
| | Electrical & Electronic Equipment) |
| 91 | Terminology |

INDEX

Copyright

The contents of this manual are subject to change without notice to improve quality.

© 2013 Samsung Electronics

Samsung Electronics owns the copyright for this manual.

Use or reproduction of this manual in parts or entirety without the authorization of Samsung Electronics is prohibited.

Microsoft and Windows are registered trademarks of Microsoft Corporation.

VESA, DPM and DDC are registered trademarks of the Video Electronics Standards Association.

- An administration fee may be charged if either
 - (a) an engineer is called out at your request and there is no defect in the product.(i.e. where you have failed to read this user manual)
 - (b) you bring the unit to a repair center and there is no defect in the product.
 (i.e. where you have failed to read this user manual)
- The amount of such administration charge will be advised to you before any work or home visit
 is carried out.

Icons used in this manual



The following images are for reference only. Real-life situations may differ from what is shown in the images.

Cleaning

Exercise care when cleaning as the panel and exterior of advanced LCDs are easily scratched.

Take the following steps when cleaning.




- 1. Power off the monitor and computer.
- 2. Disconnect the power cord from the monitor.



Hold the power cable by the plug and do not touch the cable with wet hands. Otherwise, an electric shock may result.



3. Wipe the monitor with a clean, soft and dry cloth.





Do not spray water or detergent directly on the product.



4. Wet a soft and dry cloth in water and wring thoroughly to clean the exterior of the monitor.




- 5. Connect the power cord to the product after cleaning the product.
- 6. Power on the monitor and computer.

Securing the Installation Space

Ensure some space around the product for ventilation. An internal temperature rise may cause fire and damage the product. Be sure to allow the amount of space as shown below or greater when installing the product.



The exterior may differ depending on the product.



Precautions for storage



Be sure to contact Samsung Customer Service Center (page 82) if the inside of the monitor needs cleaning. (Service fee will be charged.)

Safety Precautions

Caution

RISK OF ELECTRIC SHOCK DO NOT OPEN

Caution: TO REDUCE THE RISK OF ELECTRIC SHOCK, DO NOT REMOVE COVER (OR BACK). THERE ARE NO USER SERVICEABLE PARTS INSIDE. REFER ALL SERVICING TO QUALIFIED PERSONNEL.



This symbol indicates that high voltage is present inside. It is dangerous to make any kind of contact with any internal part of this product.



This symbol alerts you that important literature concerning operation and maintenance has been included with this product.

Symbols for safety precautions

| Warning | A serious or fatal injury may result if instructions are not followed. |
|---------|--|
| Caution | Personal injury or damage to properties may result if instructions are not followed. |
| 0 | Activities marked by this symbol are prohibited. |
| 0 | Instructions marked by this symbol must be followed. |

Electricity and Safety



The following images are for reference only. Real-life situations may differ from what is shown in the images.



Warning



Do not use a damaged power cord or plug, or a loose power socket.

An electric shock or fire may result.



Do not plug many products into the same power socket.

Otherwise, the socket may overheat and cause a fire.



Do not touch the power plug with wet hands.

• Otherwise, an electric shock may result.



Insert the power plug all the way in so it is not loose.

An unstable connection may cause a fire.



Connect the power plug to a grounded power socket (type 1 insulated devices only).

An electric shock or injury may result.



Do not bend or pull the power cord with force. Do not weigh the power cord down with a heavy object.

A damaged power cord may cause an electric shock or fire.



Do not place the power cord or product near heat sources.

An electric shock or fire may result.



Remove foreign substances such as dust around the plug pins and power socket with a dry cloth.

Otherwise, a fire may result.





Do not unplug the power cord when the product is in use.

• The product may become damaged by an electric shock.



Do not use the power cord for products other than authorized products supplied by Samsung.

An electric shock or fire may result.



Keep the power socket where the power cord is connected unobstructed.

• If any problem occurs in the product, unplug the power cable to completely cut the power to the product.

Power to the product cannot be completely cut off with the power button.



Hold the plug when disconnecting the power cord from the power socket.

An electric shock or fire may result.

Installation and Safety





DO NOT PLACE CANDLES, INSECT REPELLANTS OR CIGARETTES ON TOP OF THE PRODUCT. DO NOT INSTALL THE PRODUCT NEAR HEAT SOURCES.

Otherwise, a fire may result.



Avoid installing the product in a narrow space with bad ventilation, such as a bookshelf or wall closet.

• Otherwise, a fire may result due to an increased internal temperature.



Keep the plastic packaging bag for the product in a place that cannot be reached by children.

Children may suffocate.



Do not install the product on an unstable or vibrating surface (insecure shelf, sloped surface, etc.).

- The product may fall and break or cause a personal injury.
- Using the product in an area with excess vibration may damage the product or cause a fire.



Do not install the product in a vehicle or a place exposed to dust, moisture (water drips, etc.), oil, or smoke.

An electric shock or fire may result.



Do not expose the product to direct sunlight, heat, or a hot object such as a stove.

• Otherwise, the product lifespan may be reduced, or a fire may result.



Do not install the product within the reach of young children.

The product may fall and injure children.



Edible oil, such as soybean oil, can damage or deform the product. Do not install the product in a kitchen or near a kitchen counter.





Take care not to drop the product when moving it.

Otherwise, product failure or personal injury may result.



Do not set down the product on its front.

The screen may become damaged.



When installing the product on a cabinet or shelf, make sure that the bottom edge of the front of the product is not protruding.

- The product may fall and break or cause a personal injury.
- Install the product only on cabinets or shelves of the right size.



Put down the product carefully.

The product may fall and break or cause a personal injury.



Installing the product in an unusual place (a place exposed to a lot of fine particles, chemical substances or extreme temperatures, or an airport or train station where the product should operate continuously for an extended period of time) may seriously affect its performance.

• Be sure to consult Samsung Customer Service Center (page 82) before installation if you want to install the product at such a place.

Operation





High voltage runs through the product. Do not attempt to disassemble, repair, or modify the product on your own.

- An electric shock or fire may result.
- Contact Samsung Customer Service Center (page 82) for repair.



Before moving the product, turn off the power switch and disconnect the power cable and all other connected cables.

 Otherwise, the power cord may be damaged and a fire or electric shock may result.



If the product generates a strange noise, a burning smell, or smoke, remove the power cord immediately and contact Samsung Customer Service Center (page 82).

An electric shock or fire may result.



Do not let children hang from the product or climb on top of it.

 The product may fall, and your child may become injured or seriously harmed.



If the product falls or the exterior is damaged, power off the product, remove the power cord, and contact Samsung Customer Service Center (page 82).

Otherwise, an electric shock or fire may result.



Do not put a heavy object, toy, or sweets on top of the product.

The product or heavy objects may fall as children try to reach for the toy or sweets resulting in a serious injury.



During a lightning or thunderstorm, power off the product and remove the power cable.

An electric shock or fire may result.



Do not drop objects on the product or apply impact.

An electric shock or fire may result.



Do not move the product by pulling the power cord or any cable.

Otherwise, the power cable may be damaged and product failure, an electric shock or fire may result.



If a gas leakage is found, do not touch the product or power plug. Also, ventilate the area immediately.

Sparks can cause an explosion or fire.



Do not lift or move the product by the power cord or any cable.

Otherwise, the power cable may be damaged and product failure, an electric shock or fire may result.



Do not use or keep combustible spray or an inflammable substance near the product.

An explosion or fire may result.



Ensure the vents are not blocked by tablecloths or curtains.

• Otherwise, a fire may result from an increased internal temperature.



Do not insert a metallic object (a chopstick, coin, hair pin, etc.) or inflammable object (paper, match, etc.) into the vent or ports of the product.

- If water or any foreign substance enters the product, be sure to power off the product, remove the power cord, and contact Samsung Customer Service Center (page 82).
- Product failure, an electric shock or fire may result.



Do not place objects containing liquid (vases, pots, bottles, etc) or metallic objects on top of the product.

- If water or any foreign substance enters the product, be sure to power off the product, remove the power cord, and contact Samsung Customer Service Center (page 82).
- Product failure, an electric shock or fire may result.





Leaving the screen fixed on a stationary image for an extended period of time may cause afterimage burn-in or defective pixels.

• If you are not going to use the product for an extended period of time, activate power-saving mode or a moving-picture screen saver.



Disconnect the power cord from the power socket if you do not plan on using the product for an extended period of time (vacation, etc).

• Otherwise, a fire may result from accumulated dust, overheating, an electric shock, or electric leakage.



Use the product at the recommended resolution and frequency.

Your eyesight may deteriorate.



Do not put DC power adapters together.

Otherwise, a fire may result.



Remove the plastic bag from the DC power adapter before you use it.

• Otherwise, a fire may result.



Do not let water enter the DC power device or get the device wet.

- An electric shock or fire may result.
- Avoid using the product outdoors where it can be exposed to rain or snow.
- Be careful not to get the DC power adapter wet when you wash the floor.



Do not put the DC power adapter near to any heating apparatus.

Otherwise, a fire may result.



Keep the DC power adapter in a well-ventilated area.



Looking at the screen too close for an extended period of time can deteriorate your eyesight.



Do not hold the monitor upside-down or move it by holding the stand.

The product may fall and break or cause a personal injury.



Do not use humidifiers or stoves around the product.

An electric shock or fire may result.



Rest your eyes for more than 5 minutes for every 1 hour of product use.

Eye fatigue will be relieved.



Do not touch the screen when the product has been turned on for an extended period of time as it will become hot.



Store the small accessories used with the product out of reach of children.



Exercise caution when adjusting the product angle or stand height.

- Otherwise, children's fingers or hands may become stuck and injured.
- Tilting the product excessively may cause it to fall and result in personal injury.



Do not place heavy objects on the product.

Product failure or personal injure may result.

Correct posture to use the product



Use the product in the correct posture as follows:

- Straighten your back.
- Allow a distance of 45 to 50 cm between your eye and the screen, and look slightly downward at the screen.
 - Keep your eyes directly in front of the screen.
- Adjust the angle so light does not reflect on the screen.
- Keep your forearms perpendicular to your upper arms and level with the back of your hands.
- Keep your elbows at about a right angle.
- Adjust the height of the product so you can keep your knees bent at 90 degrees or more, your heels attached to the floor, and your arms lower than your heart.


1.1 Checking the Contents

1.1.1 Removing the Packaging

1 Open the packaging box. Be careful not to damage the product when you open the packaging with a sharp instrument.



2 Remove the styrofoam from the product.



- 3 Check the components and remove the styrofoam and plastic bag.
 - This image is for reference only.



4 Store the box in a dry area so that it can be used when moving the product in the future.

1.1.2 Checking the Components



- Contact the dealer from whom you purchased the product if any item is missing.
- The appearance of the components and items sold separately may differ from the image shown.

Components



Stand neck
(North America only)



Components may vary depending on the country.

Stand neck

(Other areas)


1.2 Parts

1.2.1 Frontal Button



The color and shape of parts may differ from what is shown.

Specifications are subject to change without notice to improve quality.



| Icons | Description | |
|---|--|--|
| Open or clo OSD contr Enab for 10 Disab butto | Description Descr | |


| Icons | Description |
|--------------------|---|
| | Configure Customized Key and press []. The following options will be enabled. |
| <u></u> | SAMSUNG Angle - SAMSUNG Bright - Eco Saving - Image Size |
| | To configure Customized Key, go to SETUP & RESET → Customized Key and select the mode you want. |
| ▲ /▼ | Move to the upper or lower menu or adjust the value for an option on the OSD menu. |
| ' . | Use this button to control the brightness and contrast of the screen. |
| | Confirm a menu selection. |
| ≒/⊡ | Pressing the [☐/☐] button when the OSD menu is not displayed will change the input source (Analog/HDMI). If you power on the product or change the input source by pressing the [☐/☐] button, a message that shows the changed input source will appear at the top left corner of the screen. |
| AUTO | Press the [AUTO] button to automatically adjust the screen settings. Changing the resolution in Display Properties will activate the Auto Adjustment function. Available only in Analog mode. |
| Ф | Turn the screen on or off. |
| | When a control button on the product is pressed, the Function Key Guide will be displayed before the onscreen menu opens. (The guide shows the function of the button pressed.) |
| Function Key Guide | To access the onscreen menu when the guide is displayed, press the corresponding button again. |
| | The Function Key Guide may vary depending on the function or product model. |
| | Refer to the actual product. |

1.2.2 Reverse Side



- The color and shape of parts may differ from what is shown.

 Specifications are subject to change without notice to improve quality.
- Provided ports may vary depending on the product.




| Port | Description |
|---------|---|
| DC 14V | Connects to the DC power adapter. |
| HDMI IN | Connects to a source device via a HDMI cable. |
| RGB IN | Connect to a PC using the D-SUB cable. |

1.3 Installation

1.3.1 Attaching the Stand




Before assembling the product, place the product down on a flat and stable surface so that the screen is facing downwards.




Insert the stand neck into the stand base in the direction shown in the figure.




Check that the stand neck is firmly connected.



Tightly fasten the connecting screw at the bottom of the stand base.




Place a soft cloth over the table Hold the main body of the to protect the product and place the product onto the cloth so that the front of the product is facing downwards.



product with your hand as shown by the figure.


Push the assembled stand into the main body in the direction of the arrow as shown in the figure.




Do not hold the product upside down only by the stand.

- Caution


1.3.2 Removing the Stand




Place a soft cloth over the table to protect the product and place the product onto the cloth so that the front of the product faces downwards.



While holding the stand neck with one hand, pound the other fisted hand down onto the top of the stand base in the direction of the arrow to detach the stand base.



Turn the connecting screw at the bottom of the stand base to separate it.




Remove the stand neck from the stand base by pulling it in the direction of the arrow as shown in the figure.

1.3.3 Adjusting the Product Tilt




The color and shape of parts may differ from what is shown. Specifications are subject to change without notice to improve quality.



- You can adjust the tilt of your monitor.
- Hold the lower part of the product and adjust the tilt carefully.

1.3.4 Anti-theft Lock

An anti-theft lock allows you to use the product securely even in public places. The locking device shape and locking method depend on the manufacturer. Refer to the user guide provided with your anti-theft locking device for details. The lock device is sold separately.



The color and shape of parts may differ from what is shown. Specifications are subject to change without notice to improve quality.


To lock an anti-theft locking device:

- 1 Fix the cable of your anti-theft locking device to a heavy object such as a desk.
- 2 Put one end of the cable through the loop on the other end.
- 3 Insert the Kensington Lock into the security slot on the back of the display.
- 4 Lock the locking device.



- An anti-theft locking device can be purchased separately.
- Refer to the user guide provided with your anti-theft locking device for details.
- Anti-theft locking devices can be purchased at electronics retailers or online.

2.1 Before Connecting



2.1.1 Pre-connection Checkpoints

- Before connecting a source device, read the user manual provided with it.
 The number and locations of ports on source devices may differ from device to device.
- Do not connect the power cable until all connections are completed.
 Connecting the power cable during connection may damage the product.
- Check the types of ports at the back of the product you want to connect.

2.2 Connecting and Using a PC

Select a connection method suitable for your PC.




Connecting parts may differ in different products.

2.2.1 Connection Using the D-SUB Cable (Analog Type)



Do not connect the power cable before connecting all other cables.

Ensure you connect a source device first before connecting the power cable.



- 1 Connect the D-SUB cable to the [RGB IN] port on the back of the product and the RGB port on the PC.
- Connect the DC power adapter to the product and a power socket.
 Next, turn on the power switch on the PC. (For details, refer to 2.2.4 Connecting the Power".)
- 3 Press [□/□] to change the input source to Analog.




Provided ports may vary depending on the product.

2.2.2 Connection Using the HDMI Cable



Do not connect the power cable before connecting all other cables.

Ensure you connect a source device first before connecting the power cable.



- 1 Connect the HDMI cable to the [HDMI IN] port on the back of the product and the HDMI port on the PC.
- Connect the DC power adapter to the product and a power socket.
 Next, turn on the power switch on the PC. (For details, refer to "2.2.4 Connecting the Power".)
- 3 Press [□/□] to change the input source to HDMI.
- _K


Provided ports may vary depending on the product.

2.2.3 Connection Using an HDMI-DVI Cable



Do not connect the power cable before connecting all other cables.

Ensure you connect a source device first before connecting the power cable.



- 1 Connect the HDMI-DVI cable to the [HDMI IN] port on the back of the product and the DVI port on the PC.
- Connect the DC power adapter to the product and a power socket.
 Next, turn on the power switch on the PC. (For details, refer to "2.2.4 Connecting the Power".)
- 3 Press [□/⊡] to change the input source to HDMI.
- _R


Provided ports may vary depending on the product.

2.2.4 Connecting the Power

Connect the power adapter to [DC 14V] jack on the rear of the product.

Connect the power cable to the DC power adapter. Next, connect the DC power adapter to the product.

Plug in the power cable to the power socket.






The input voltage is switched automatically.

2.2.5 Driver Installation



- You can set the optimum resolution and frequency for this product by installing the corresponding drivers
- An installation driver is contained on the CD supplied with the product.
- If the file provided is faulty, visit the Samsung homepage (http://www.samsung.com/) and download the file.
- 1 Insert the user manual CD provided with the product into the CD-ROM drive.
- 2 Click "Windows Driver".
- 3 Follow the instructions given on the screen to proceed with installation.
- Select your product model from the list of models.




Go to Display Properties and check that the resolution and refresh rate are appropriate.
Refer to your Windows OS manual for further details.

2.2.6 Setting Optimum Resolution

An information message about setting optimum resolution will appear if you power on the product for the first time after purchase.

Select a language on the product and change the resolution on your PC to the optimum setting.



- Press [▲/▼] to move to the language you want and press [□/⊡].
- 2 To hide the information message, press [MENU].



- If the optimum resolution is not selected, the message will appear up to three times for a specified time even when the product is turned off and on again.
- The optimum resolution can also be selected in **Control Panel** on your PC.

2.2.7 Changing the Resolution Using a PC




- Adjust the resolution and refresh rate in Control Panel on your PC to obtain optimum picture quality.
- The picture quality of TFT-LCDs may degrade if the optimum resolution is not selected.

Changing the Resolution on Windows XP

Go to **Control Panel** \rightarrow **Display** \rightarrow **Settings** and change the resolution.








Changing the Resolution on Windows Vista

Go to Control Panel \rightarrow Personalization \rightarrow Display Settings and change the resolution.










2

Connecting and Using a Source Device

Changing the Resolution on Windows 7

Go to Control Panel \rightarrow Display \rightarrow Screen Resolution and change the resolution.









2


Connecting and Using a Source Device


Changing the Resolution on Windows 8


Go to Settings \rightarrow Control Panel \rightarrow Display \rightarrow Screen Resolution and change the resolution.











Configure the screen settings such as brightness.

3.1 Brightness

You can adjust the general brightness of the picture. (Range: 0~100)

A higher value will make the picture appear brighter.



- This menu is not available when MAGICBright is set to Dynamic Contrast mode.
- This menu is not available when **Eco Saving** is enabled.

3.1.1 Configuring Brightness

1 Press any button on the front of the product to display the Function Key Guide.

Next, press [MENU] to display the corresponding menu screen.

- 2 Press [▲/▼] to move to PICTURE and press [□/□] on the product.
- 3 Press [▲/▼] to move to Brightness and press [□/峄] on the product.
 The following screen will appear.



- 4 Adjust the **Brightness** using the [▲/▼] buttons.
- 5 The selected option will be applied.

3.2 Contrast

Adjust the contrast between the objects and background. (Range: 0~100)

A higher value will increase the contrast to make the object appear clearer.



This option is not available when MAGIC Bright is in Cinema or Dynamic Contrast mode.

3.2.1 Configuring Contrast

Press any button on the front of the product to display the Function Key Guide.
Next, press [MENU] to display the corresponding menu screen.

- Press [▲/▼] to move to PICTURE and press [□/□] on the product.
- 3 Press [▲/▼] to move to Contrast and press [□/급] on the product.

 The following screen will appear.



- 4 Adjust the Contrast using the [▲/▼] buttons.
- 5 The selected option will be applied.

3.3 Sharpness

Make the outline of objects more clear or blurry. (Range: 0~100)

A higher value will make the outline of objects clearer.



- This option is not available when MAGICBright is in Cinema or Dynamic Contrast mode.
- This menu is not available when
 ^{SAMSUNG}
 Upscale is in Mode1 or Mode2.

3.3.1 Configuring Sharpness

1 Press any button on the front of the product to display the Function Key Guide.

Next, press [MENU] to display the corresponding menu screen.

- Press [▲/▼] to move to PICTURE and press [☐/☐] on the product.
- 3 Press [▲/▼] to move to Sharpness and press [□/◄] on the product.
 The following screen will appear.



- 4 Adjust the **Sharpness** using the [▲/▼] buttons.
- 5 The selected option will be applied.

3.4 SAMSUNG MAGIC Bright

This menu provides an optimum picture quality suitable for the environment where the product will be used.



- This menu is not available when Eco Saving is enabled.
- This menu is not available when MAGICAngle is enabled.

You can customize the brightness to suit your preferences.

3.4.1 Configuring SAMSUNG MAGIC Bright

- Press any button on the front of the product to display the Function Key Guide.
 Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to PICTURE and press [☐/☐] on the product.
- 3 Press [▲/▼] to move to MAGICBright and press [□/⊡] on the product.
 The following screen will appear.



- Custom: Customize the contrast and brightness as required.
- Standard: Obtain a picture quality suitable for editing documents or using Internet.
- Game: Obtain a picture quality suitable for playing games that involve many graphic effects and dynamic movements.
- Cinema: Obtain the brightness and sharpness of TVs suitable for enjoying video and DVD content.
- Dynamic Contrast: Obtain balanced brightness through automatic contrast adjustment.



When the external input is connected through HDMI and PC/AV Mode is set to AV, MAGICBright has four automatic picture settings (Dynamic, Standard, Movie and Custom) that are preset at the factory. You can activate either Dynamic, Standard, Movie or Custom. You can select Custom which automatically recalls your personalized picture settings.

- Dynamic: Select this mode to view a sharper image than in Standard mode.
- Standard: Select this mode when the surroundings are bright. This also provides a sharp image.
- Movie: Select this mode when the surroundings are dark. This will save power and reduce eye fatigue.
- Custom: Select this mode when you want to adjust the image according to your preferences.
- 4 Press [▲/▼] to move to the option you want and press [□/⊡].
- 5 The selected option will be applied.

3.5 SAMSUNG MAGIC Angle

SAMSUNG Angle allows you to configure the settings to obtain the optimum picture quality according to your viewing angle.



This option is not available when SAMSUNGBright is in Cinema or Dynamic Contrast mode.


This feature provides the viewing angle, brightness, and tint to suit your preferences.

3.5.1 Configuring SAMSUNG MAGIC Angle

- 1 Press any button on the front of the product to display the Function Key Guide.

 Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to PICTURE and press [☐/⊡] on the product.
- 3 Press [▲/▼] to move to MAGICAngle and press [□/⊡] on the product.
 The following screen will appear.





- Off ①: Select this option to view directly in front of the product.
- Lean Back Mode 1 2: Select this option to view from a place slightly lower than the product.
- Lean Back Mode 2 3: Select this option to view from a place lower than Lean Back Mode 1.
- Standing Mode ①: Select this option to view from a place higher than the product.
- Side Mode (5): Select this option to view from either side of the product.
- Group View: Select this option for more than one viewer to view from places ①, ④ and ⑤.
- Custom: Lean Back Mode 1 will be applied by default if Custom is selected.
- Press [▲/▼] to move to the option you want and press [□/□].
- 5 The selected option will be applied.

3.6 SAMSUNG MAGIC Upscale

SAMSUNGUPScale function can enhance the layers of the picture details and the vividness of the picture.



- The function has more obvious effects on low-resolution pictures.
- This menu is not available when MAGICBright is in Cinema or Dynamic Contrast mode.

3.6.1 Configuring SAMSUNG MAGIC Upscale

1 Press any button on the front of the product to display the Function Key Guide.

Next, press [MENU] to display the corresponding menu screen.

- 2 Press [▲/▼] to move to PICTURE and press [☐/⊡] on the product.
- 3 Press [▲/▼] to move to MAGICUpscale and press [☐/☐] on the product.

 The following screen will appear.



Comparing with Mode1, Mode2 has a stronger effect.

- 4 Press [▲/▼] to move to the option you want and press [□/-].
- 5 The selected option will be applied.

3.7 Image Size

Change the picture size.

3.7.1 Changing the Image Size

- 1 Press any button on the front of the product to display the Function Key Guide.
 - Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to PICTURE and press [□/៤] on the product.
- 3 Press [▲/▼] to move to Image Size and press [□/◄] on the product.
 The following screen will appear.





- Auto: Display the picture according to the aspect ratio of the input source.
- Wide: Display the picture in full screen regardless of the aspect ratio of the input source.

In AV mode



- 4:3: Display the picture with an aspect ratio of 4:3. Suitable for videos and standard broadcasts.
- **16:9**: Display the picture with an aspect ratio of 16:9.
- Screen Fit: Display the picture with the original aspect ratio without cutting off.



- Changing the screen size is available when the following conditions are satisfied.
- The function may not be supported depending on the ports provided with the product.
 - A digital output device is connected using the HDMI cable.

- The input signal is 480p, 576p, 720p, or 1080p and monitor can display normally (Not every model can support all of these signals.).
- This can only be set when the external input is connected through HDMI and PC/AV Mode is set to AV.
- 4 Press [▲/▼] to move to the option you want and press [□/⊡].
- 5 The selected option will be applied.

3.8 HDMI Black Level

If a DVD player or set-top box is connected to the product via HDMI, image quality degradation (contrast/color degradation, black level, etc.) may occur, depending on the connected source device. If this is the case, correct the degraded picture quality using **HDMI Black Level**.



This function is only available in **HDMI** mode.

3.8.1 Configuring the HDMI Black Level Settings

- 1 Press any button on the front of the product to display the Function Key Guide.
 - Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to PICTURE and press [☐/☐] on the product.
- 3 Press [▲/▼] to move to HDMI Black Level and press [□/⊡] on the product. The following screen will appear.



- Normal: Select this mode when there is no contrast ratio degradation.
- Low: Select this mode to reduce the black level and increase the white level when there is a contrast ratio degradation.
- 4 Press [▲/▼] to move to the option you want and press [□/⊡].
- 5 The selected option will be applied.
- HDMI Black Level may not be compatible with some source devices.

3.9 H-Position & V-Position

H-Position: Move the screen to the left or right.

V-Position: Move the screen up or down.



- This menu is available in Analog mode only.
- This menu is only available when Image Size is set to Screen Fit in AV Mode. When a 480P or 576P or 720P or 1080P signal is input in AV mode and the monitor can display normally, select Screen Fit to adjust horizontal position in 0-6 levels.

3.9.1 Configuring H-Position & V-Position

Press any button on the front of the product to display the Function Key Guide.

Next, press [MENU] to display the corresponding menu screen.

- 2 Press [▲/▼] to move to PICTURE and press [☐/☐] on the product.
- 3 Press [▲/▼] to move to H-Position or V-Position, and press [□/⊡].
 The following screen will appear.





- 4 Press [▲/▼] to configure H-Position or V-Position.
- 5 The selected option will be applied.

3.10 Coarse

Adjust the screen frequency.



This menu is available in **Analog** mode only.

3.10.1 Adjusting Coarse

- Press any button on the front of the product to display the Function Key Guide.
 Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to PICTURE and press [□/⊡] on the product.
- 3 Press [▲/▼] to move to Coarse and press [□/⊡] on the product.
 The following screen will appear.



- 4 Adjust the Coarse using the [▲/▼] buttons.
- 5 The selected option will be applied.

3.11 Fine

Fine-adjust the screen to obtain a vivid picture.



This menu is available in **Analog** mode only.

3.11.1 Adjusting Fine

- 1 Press any button on the front of the product to display the Function Key Guide.
 - Next, press $\left[\mbox{MENU} \right]$ to display the corresponding menu screen.
- 2 Press [▲/▼] to move to PICTURE and press [☐/☐] on the product.
- 3 Press [▲/▼] to move to Fine and press [□/☞] on the product.

 The following screen will appear.



- 4 Adjust the Fine using the [▲/▼] buttons.
- 5 The selected option will be applied.

Adjust the tint of the screen. This menu is not available when MAGICBright is set to Cinema or Dynamic Contrast mode.

4.1 Red

Adjust the value of the color red in the picture. (Range: 0~100)

A higher value will increase the intensity of the color.

4.1.1 Configuring Red

1 Press any button on the front of the product to display the Function Key Guide.

Next, press [MENU] to display the corresponding menu screen.

- Press [▲/▼] to move to COLOR and press [☐/☐] on the product.
- 3 Press [▲/▼] to move to Red and press [□/⊡] on the product.
 The following screen will appear.



- 4 Adjust the Red using the [▲/▼] buttons.
- 5 The selected option will be applied.

4.2 Green

Adjust the value of the color green in the picture. (Range: 0~100)

A higher value will increase the intensity of the color.

4.2.1 Configuring Green

- 1 Press any button on the front of the product to display the Function Key Guide.

 Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to COLOR and press [□/⊡] on the product.
- 3 Press [▲/▼] to move to **Green** and press [□/☞] on the product. The following screen will appear.



- 4 Adjust the Green using the [▲/▼] buttons.
- 5 The selected option will be applied.

4.3 Blue

Adjust the value of the color blue in the picture. (Range: 0~100)

A higher value will increase the intensity of the color.

4.3.1 Configuring Blue

- 1 Press any button on the front of the product to display the Function Key Guide.
 - Next, press [MENU] to display the corresponding menu screen.
- Press [▲/▼] to move to COLOR and press [☐/☐] on the product.
- 3 Press [▲/▼] to move to Blue and press [□/□] on the product.
 The following screen will appear.



- 4 Adjust the Blue using the [▲/▼] buttons.
- 5 The selected option will be applied.

4.4 Color Tone

Adjust the general color tone of the picture.



This menu is not available when MAGICAngle is enabled.

4.4.1 Configuring the Color Tone Settings

1 Press any button on the front of the product to display the Function Key Guide.

Next, press [MENU] to display the corresponding menu screen.

- Press [▲/▼] to move to COLOR and press [☐/☐] on the product.
- 3 Press [▲/▼] to move to Color Tone and press [□/◄] on the product.
 The following screen will appear.



- Cool 2: Set the color temperature to be cooler than Cool 1.
- Cool 1: Set the color temperature to be cooler than Normal mode.
- Normal: Display the standard color tone.
- Warm 1: Set the color temperature to be warmer than Normal mode.
- Warm 2: Set the color temperature to be warmer than Warm 1.
- Custom: Customize the color tone.



- When the external input is connected through HDMI and PC/AV Mode is set to AV, Color Tone has four color temperature settings (Cool, Normal, Warm and Custom).
- The function may not be supported depending on the ports provided with the product.
- 4 Press [▲/▼] to move to the option you want and press [□/⊡].
- 5 The selected option will be applied.

4.5 Gamma

Adjust the mid-range brightness (Gamma) of the picture.



This menu is not available when ${\tt MAGIC}^{\tt SAMSUNG}{\tt Angle}$ is enabled.

4.5.1 Configuring Gamma

- Press any button on the front of the product to display the Function Key Guide.
 Next, press [MENU] to display the corresponding menu screen.
- Press [▲/▼] to move to COLOR and press [☐/☐] on the product.
- 3 Press [▲/▼] to move to Gamma and press [□/⊡] on the product.
 The following screen will appear.



- 4 Press [▲/▼] to move to the option you want and press [□/--].
- 5 The selected option will be applied.

5.1 Language

Set the menu language.



- A change to the language setting will only be applied to the onscreen menu display.
- It will not be applied to other functions on your PC.

5.1.1 Configuring Language

- Press any button on the front of the product to display the Function Key Guide.
 Next, press [MENU] to display the corresponding menu screen.
- Press [▲/▼] to move to MENU SETTINGS and press [□/⊡] on the product.
- 3 Press [▲/▼] to move to Language and press [☐/⊡] on the product.

 The following screen will appear.



- 4 Press [▲/▼] to move to the language you want and press [□/□].
- 5 The selected option will be applied.

5.2 Menu H-Position & Menu V-Position

Menu H-Position: Move the menu position to the left or right.

Menu V-Position: Move the menu position up or down.


5.2.1 Configuring Menu H-Position & Menu V-Position

1 Press any button on the front of the product to display the Function Key Guide.

Next, press [MENU] to display the corresponding menu screen.

- 2 Press [▲/▼] to move to MENU SETTINGS and press [□/급] on the product.
- 3 Press [▲/▼] to move to Menu H-Position or Menu V-Position, and press [□/⊡] on the product.

The following screen will appear.





- 4 Press [▲/▼] to configure Menu H-Position or Menu V-Position.
- 5 The selected option will be applied.

5.3 Display Time

Set the on-screen display (OSD) menu to automatically disappear if the menu is not used for a specified period of time.

Display Time can be used to specify the time after which you want the OSD menu to disappear.

5.3.1 Configuring Display Time

- Press any button on the front of the product to display the Function Key Guide.
 Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to MENU SETTINGS and press [□/ᢎ] on the product.
- 3 Press [▲/▼] to move to Display Time and press [□/⊡] on the product.
 The following screen will appear.



- 4 Press [▲/▼] to move to the option you want and press [□/-].
- 5 The selected option will be applied.

5.4 Transparency

Set the transparency for the menu windows:

5.4.1 Changing Transparency

- Press any button on the front of the product to display the Function Key Guide.
 Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to MENU SETTINGS and press [□/⊡] on the product.
- 3 Press [▲/▼] to move to **Transparency** and press [♠/♠] on the product. The following screen will appear.



- 4 Press [▲/▼] to move to the option you want and press [□/⊡].
- 5 The selected option will be applied.


6.1 Reset

Return all the settings for the product to the default factory settings.

6.1.1 Initializing Settings (Reset)

- 1 Press any button on the front of the product to display the Function Key Guide.
 - Next, press $[{\it MENU}]$ to display the corresponding menu screen.
- 2 Press [▲/▼] to move to **SETUP&RESET** and press [□/급] on the product.
- 3 Press [▲/▼] to move to Reset and press [☐/⊡] on the product.
 The following screen will appear.





- 4 Press [▲/▼] to move to the option you want and press [□/-].
- 5 The selected option will be applied.

6.2 Eco Saving

The **Eco Saving** function reduces power consumption by controlling the electric current used by the monitor panel.



This menu is not available when MAGIC Bright is in Dynamic Contrast mode.

6.2.1 Configuring Eco Saving

- Press any button on the front of the product to display the Function Key Guide.
 Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to **SETUP&RESET** and press [□/급] on the product.
- 3 Press [▲/▼] to move to Eco Saving and press [□/⊡] on the product.
 The following screen will appear.




- 75%: Change the monitor power consumption to 75% of the default level.
- 50%: Change the monitor power consumption to 50% of the default level.
- Off: Deactivate the Eco Saving function.
- 4 Press [▲/▼] to move to the option you want and press [□/-].
- 5 The selected option will be applied.

6.3 Off Timer

You can set the product to automatically turn off.

6.3.1 Configuring Off Timer

- 1 Press any button on the front of the product to display the Function Key Guide.
 - Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to **SETUP&RESET** and press [□/-] on the product.
- 3 Press [▲/▼] to move to Off Timer and press [□,/⊡] on the product.
 The following screen will appear.



- Off: Deactivate the off timer so that the product does not power off automatically.
- On: Activate the off timer so that the product powers off automatically.
- 4 Press [▲/▼] to move to the option you want and press [□/⊡].
- 5 The selected option will be applied.

6.4 Turn Off After


The off timer can be set within a range of 1 to 23 hours. The product will automatically power off after the specified number of hours.



This option is only available when **Off Timer** is set to **On**.

6.4.1 Configuring Turn Off After

- 1 Press any button on the front of the product to display the Function Key Guide.
 - Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to SETUP&RESET and press [□/៤] on the product.
- 3 Press [▲/▼] to move to Turn Off After and press [□/☞] on the product.
 The following screen will appear.



- 4 Press [▲/▼] to configure Turn Off After.
- 5 The selected option will be applied.

6.5 PC/AV Mode

Set PC/AV Mode to AV. The picture size will be enlarged. This option is useful when you view a movie.



- This function does not support Analog mode.
- Supplied for the wide models only such as 16:9 or 16:10.


6.5.1 Configuring PC/AV Mode

1 Press any button on the front of the product to display the Function Key Guide.

Next, press $\left[\mbox{MENU} \right]$ to display the corresponding menu screen.

- 2 Press [▲/▼] to move to SETUP&RESET and press [□/៤] on the product.
- 3 Press [▲/▼] to move to PC/AV Mode and press [□/◄] on the product.
 The following screen will appear.






- 4 Press [▲/▼] to move to the option you want and press [□/⊡].
- 5 The selected option will be applied.

6.6 Key Repeat Time

Control the response rate of a button when the button is pressed.

6.6.1 Configuring Key Repeat Time

- 1 Press any button on the front of the product to display the Function Key Guide.
 - Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to SETUP&RESET and press [□/៤] on the product.
- 3 Press [▲/▼] to move to Key Repeat Time and press [□/⊡] on the product.
 The following screen will appear.



- Acceleration, 1 sec, or 2 sec can be selected. If No Repeat is selected, a command responds
 only once when a button is pressed.
- 4 Press [▲/▼] to move to the option you want and press [□/⊡].
- 5 The selected option will be applied.

6.7 Source Detection

You can activate Source Detection.

6.7.1 Configuring Source Detection

- 1 Press any button on the front of the product to display the Function Key Guide.

 Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to SETUP&RESET and press [□/급] on the product.
- 3 Press [▲/▼] to move to Source Detection and press [□/⊡] on the product.
 The following screen will appear.



- Auto: The input source is automatically recognized.
- Manual: Manually select an input source.
- 4 Press [▲/▼] to move to the option you want and press [□/⊡].
- 5 The selected option will be applied.

6.8 Customized Key

You can customize Customized Key as follows.

6.8.1 Configuring Customized Key

- 1 Press any button on the front of the product to display the Function Key Guide.

 Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to **SETUP&RESET** and press [□/-] on the product.
- 3 Press [▲/▼] to move to Customized Key and press [□/⊡] on the product.
 The following screen will appear.



- SAMSUNG Angle SAMSUNG Bright Eco Saving Image Size
- 4 Press [▲/▼] to move to the option you want and press [□/⊡].
- 5 The selected option will be applied.


INFORMATION Menu and Others

7.1 INFORMATION

View the current input source, frequency and resolution.

7.1.1 Displaying INFORMATION

- 1 Press any button on the front of the product to display the Function Key Guide.
 - Next, press [MENU] to display the corresponding menu screen.
- 2 Press [▲/▼] to move to INFORMATION.
 The current input source, frequency and resolution will appear.





The displayed menu items may vary depending on the model.

INFORMATION Menu and Others

7.2 Configuring Brightness and Contrast in the Initial Screen

Adjust the **Brightness**, **Contrast** using the [$\mbox{$\stackrel{.}{\simeq}$}$] buttons when the initial screen (that displays no menu screen) is displayed.

1 Press any button on the front of the product (when no menu screen is displayed) to display the Function Key Guide.

Next, press [- 2]. The following screen will appear.



- 2 Press the [☐/☐] button to alternate between the Brightness and Contrast settings.
- 3 Adjust the **Brightness**, **Contrast** using the [▲/▼] buttons.

8.1 MagicTune

8.1.1 What is "MagicTune"?



"MagicTune" is a software program that helps with monitor adjustments by providing comprehensive descriptions of monitor functions and easy-to-understand guidelines.

You can adjust the product with the mouse and the keyboard without using the operating buttons of the product.

8.1.2 Installing the Software

- 1 Insert the installation CD into the CD-ROM drive.
- 2 Select the "MagicTune" setup program.
 - If the pop-up screen for the software installation does not appear on the main screen, find and double-click the "MagicTune" setup file on the CD-ROM.
- 3 Select the installation language and click Next.
- 4 Complete the remaining software installation steps according to the instructions displayed on the screen.



- The software may not work properly if you do not restart the computer after the installation.
- The "MagicTune" icon may not appear depending on the computer system and the product specifications.
- If the shortcut icon does not appear, press the F5 key.

Restrictions and Problems with the Installation ("MagicTune™")

The installation of "MagicTune™" may be affected by the Graphics Card, Motherboard and the Networking Environment.

System Requirements

OS

• Windows XP, Windows Vista, Windows 7, Windows 8

8.1.3 Removing the Software

You can only remove "MagicTune™" through **Add or Remove Programs** in Windows.

To remove "MagicTune™", complete the following steps.

- 1 Click Start select Settings, and select Control Panel from the menu.
 For Windows XP, click Start, and select Control Panel from the menu.
- 2 Double-click the **Add or Remove Programs** icon in the Control Panel.
- In the **Add/Remove** window, find and select "MagicTune™" so that it is highlighted.
- 4 Click Change or Remove Programs to remove the software.
- 5 Select Yes to start removing "MagicTune™".
- 6 Wait until a message box appears informing you that the software has been removed completely.



For technical support, the FAQ (frequently asked questions) or information about the software upgrade for "MagicTuneTM", please visit our website (http://www.samsung.com/us/consumer/learningresources/monitor/magetune/pop_intro.html).

8.2 MultiScreen



"MultiScreen" enables users to use the monitor by partitioning multiple sections.

8.2.1 Installing the Software

- 1 Insert the installation CD into the CD-ROM drive.
- Select the "MultiScreen" setup program.
 - If the pop-up screen for the software installation does not appear on the main screen, find and double-click the "MultiScreen" setup file on the CD-ROM.
- When the Installation Wizard appears, click **Next**.
- 4 Complete the remaining software installation steps according to the instructions displayed on the screen.



- The software may not work properly if you do not restart the computer after the installation.
- The "MultiScreen" icon may not appear depending on the computer system and the product specifications.
- If the shortcut icon does not appear, press the F5 key.

Restrictions and Problems with the Installation ("MultiScreen")

The "MultiScreen" installation may be affected by the Graphics Card, Motherboard and the Networking Environment.

System Requirements

OS

- Windows™ 2000
- Windows XP Home Edition
- Windows XP Professional
- Windows Vista 32Bit
- Windows 7 32Bit
- Windows 8 32Bit



For "MultiScreen", the operating systems Windows 2000 or later is recommended.

Hardware

- At least 32MB of memory
- At least 60MB of free space on the hard disk drive

8.2.2 Removing the Software

Click Start, select Settings/Control Panel, and then double-click Add or Remove Programs.

Select "MultiScreen" from the program list and click the Add/Delete button.

9.1 Requirements Before Contacting Samsung Customer Service Center

9.1.1 Testing the Product



Before calling Samsung Customer Service Center, test your product as follows. If the problem persists, contact Samsung Customer Service Center.

Check if your product is operating normally by using the product test function.

If the screen is turned off and the power indicator blinks even though the product is properly connected to a PC, perform a self-diagnosis test.

- 1 Power off both the PC and product.
- 2 Disconnect the cables from the product.
- 3 Power on the product.
- 4 If the message Check Signal Cable appears, the product is working normally.



If the screen remains blank, check the PC system, video controller and cable.

9.1.2 Checking the Resolution and Frequency

For a mode that exceeds the supported resolution (refer to "10.3 Standard Signal Mode Table"), the message **Not Optimum Mode** will appear for a short time.

9.1.3 Check the following.

Installation issue (PC mode)

| Issues | Solutions |
|--|--|
| The screen keeps switching on and off. | Check the cable connection between the product and PC, and ensure the connectors are locked. |
| | (Refer to "2.2 Connecting and Using a PC") |

Screen issue

| Issues | Solutions | |
|---|---|--|
| The power LED is off. The screen will not switch on. | Check that the power cable is connected properly. | |
| | (Refer to "2.2 Connecting and Using a PC") | |
| The message Check Signal Cable appears. | Check that the cable is properly connected to the product. | |
| | (Refer to "2.2 Connecting and Using a PC") | |
| | Check that the device connected to the product is powered on. | |
| Not Optimum Mode is displayed. | This message appears when the signal from the graphics card exceeds the maximum resolution or frequency for the product. | |
| | Change the maximum resolution and frequency to suit the product performance, referring to Standard Signal Mode Table (page 80). | |
| The images on the screen look distorted. | Check the cable connection to the product. | |
| | (Refer to "2.2 Connecting and Using a PC") | |
| The screen is not clear. The screen is blurry. | Adjust Coarse and Fine. | |
| | Remove any accessories (video extension cable, etc.) and try again. | |
| | Set the resolution and frequency to the recommended level. | |
| The screen appears unstable and shaky. | Check that the resolution and frequency for the | |
| There are shadows or ghost images left on the screen. | PC are within the range of resolution and frequency compatible with the product. Next, if required, change the settings, referring to Standard Signal Mode Table (page 80) in this manual and the INFORMATION menu on the product. | |
| The screen is too bright. The screen is too dark. | Adjust Brightness and Contrast. | |
| Screen color is inconsistent. | Change the COLOR settings. | |
| | (Refer to " Configuring Tint") | |
| The colors on the screen have a shadow and are | Change the COLOR settings. | |
| distorted. | (Refer to " Configuring Tint") | |
| White does not really look white. | Change the COLOR settings. | |
| | (Refer to " Configuring Tint") | |

| Issues | Solutions |
|---|---|
| There is no image on the screen and the power LED blinks every 0.5 to 1 second. | The product is operating in power-saving mode. |
| | Press any key on the keyboard or move the mouse to return to normal operating mode. |

Source device issue

| Issues | Solutions |
|---|---|
| A beeping sound is heard when my PC is booting. | If a beeping sound is heard when your PC is booting, have your PC serviced. |

9.2 Q & A

| Question | Answer | |
|----------------------|--|--|
| How can I change the | Set the frequency on your graphics card. | |
| frequency? | Windows XP: Go to Control Panel → Appearance and Themes → Display → Settings → Advanced → Monitor, and adjust Refresh rate under Monitor settings. | |
| | Windows ME/2000: Go to Control Panel → Display → Settings → Advanced → Monitor, and adjust Refresh rate under Monitor settings. | |
| | Windows Vista: Go to Control Panel → Appearance and Personalization → Personalization → Display Settings → Advanced Settings → Monitor, and adjust Refresh rate under Monitor settings. | |
| | Windows 7: Go to Control Panel → Appearance and Personalization → Display → Screen Resolution → Advanced settings → Monitor, and adjust Refresh rate under Monitor settings. | |
| | Windows 8: Go to Settings → Control Panel → Appearance and Personalization → Display → Screen Resolution → Advanced settings → Monitor, and adjust Refresh rate under Monitor settings. | |

| Question | Answer |
|----------------------------------|--|
| How can I change the resolution? | Windows XP: Go to Control Panel → Appearance and Themes → Display → Settings, and adjust the resolution. |
| | Windows ME/2000: Go to Control Panel → Display → Settings, and adjust the resolution. |
| | Windows Vista: Go to Control Panel → Appearance and Personalization → Personalize → Display Settings, and adjust the resolution. |
| | Windows 7: Go to Control Panel → Appearance and Personalization → Display → Adjust Resolution, and adjust the resolution. |
| | Windows 8: Go to Settings → Control Panel → Appearance and Personalization → Display → Adjust Resolution, and adjust the resolution. |
| How do I set power-saving mode? | Windows XP: Set power-saving mode in Control Panel → Appearance and Themes → Display → Screen Saver Settings or BIOS SETUP on the PC. |
| | Windows ME/2000: Set power-saving mode in Control Panel → Display → Screen Saver Settings or BIOS SETUP on the PC. |
| | Windows Vista: Set power-saving mode in Control Panel → Appearance and Personalization → Personalize → Screen Saver Settings or BIOS SETUP on the PC. |
| | Windows 7: Set power-saving mode in Control Panel → Appearance and Personalization → Personalize → Screen Saver Settings or BIOS SETUP on the PC. |
| | Windows 8: Set power-saving mode in Settings → Control Panel → Appearance and Personalization → Personalize → Screen Saver Settings or BIOS SETUP on the PC. |



Refer to the user manual for your PC or graphics card for further instructions on adjustment.

10.1 General

| Model Name | | S27C390H | |
|-----------------------|-------------------------|--|--|
| Panel | Size | 27 Inches (68 cm) | |
| | Display area | 597.60 mm (H) x 336.15 mm (V) | |
| | | 23.53 Inches (H) x 13.23 Inches (V) | |
| | Pixel Pitch | 0.31125 mm (H) x 0.31125 mm (V) | |
| | | 0.0123 Inches (H) x 0.0123 Inches (V) | |
| Synchronization | Horizontal Frequency | 30 ~ 81 kHz | |
| | Vertical Frequency | 56 ~ 75 Hz | |
| Display Color | | 16.7 M | |
| Resolution | Optimum Resolution | 1920 x 1080 @ 60 Hz | |
| Maximum Resolution | | 1920 x 1080 @ 60 Hz | |
| Input Signal, Ter | minated | RGB Analog, HDMI (High Definition Multimedia Interface) | |
| | | 0.7 Vp-p ± 5% | |
| | | separate H/V sync, Composite, SOG | |
| | | TTL level (V high ≥ 2.0V, V low ≤ 0.8V) | |
| Maximum Pixel (| Clock | 148 MHz (Analog, HDMI) | |
| Power Supply | | This product supports 100-240 V. Since the standard voltage may differ from country to country, please check the label on the back of the product. | |
| Signal connecto | rs | 15pin-to-15pin D-sub cable, Detachable | |
| | | HDMI to DVI Cable, Detachable | |
| | | HDMI Cable, Detachable | |
| | | 643 x 398 x 55 mm | |
| (W x H x D) / | | 25.3 x 15.7 x 2.2 inches | |
| Weight | With Stand | 643 x 470 x 252 mm / 4.2 kg | |
| | | 25.3 x 18.5 x 9.9 inches / 9.3 lbs | |

| Model | Model Name S27C390H | |
|-------------------------|---------------------|--|
| Environmental Operating | | Temperature : 50°F ~ 104°F (10°C ~ 40°C) |
| considerations | | Humidity: 10 % – 80 %, non-condensing |
| | Storage | Temperature : -4°F ~ 113°F (-20°C ~ 45°C) |
| | | Humidity: 5 % – 95 %, non-condensing |
| Plug-and-Play | | This monitor can be installed and used with any Plug-and-Play compatible systems. Two-way data exchange between the monitor and PC system optimizes the monitor settings. Monitor installation takes place automatically. However, you can customize the installation settings if desired. |
| Panel Dots (Pixe | els) | Due to the nature of the manufacturing of this product, approximately 1 pixel per million (1ppm) may be brighter or darker on the LCD panel. This does not affect product performance. |



The above specifications are subject to change without notice to improve quality.



This device is a Class B digital apparatus.

(USA only)

Dispose unwanted electronics through an approved recycler.

To find the nearest recycling location, go to our website:

www.samsung.com/recyclingdirect or call, (877) 278 - 0799

10.2 PowerSaver

The power-saving function of this product reduces power consumption by switching off the screen and controlling the power LED status if the product is not used for a specified period of time.

The power is not turned off in power-saving mode. To switch the screen back on, press any key on the keyboard or move the mouse. Power-saving mode functions only when the product is connected to a PC that has a power-saving function.

| PowerSaver | Energy Star Power Consumption | Power saving mode | Power off (Power button) |
|-------------------|----------------------------------|-------------------|-----------------------------|
| Power Indicator | On | Blinking | Off |
| Power Consumption | 25 W | Typical 0.3 W | Typical 0.3 W |



- The power consumption level can vary in different operating conditions or when settings are changed.
 - (S*C390 Model Power saving mode / Power off (Power button): Max 0.45 watts.)
- ENERGY STAR® is a US registered mark of the United States Environmental Protection Agency. Energy Star power is measured with the test method in the current Energy Star® Standard.
- To reduce the power consumption to 0 watts, turn off the power switch on the back of the product
 or disconnect the power cable. Be sure to disconnect the power cable when you will not be using
 the product for an extended period of time. To reduce the power consumption to 0 watts when the
 power switch is not available, disconnect the power cable.

10.3 Standard Signal Mode Table



- This product can be set to only one resolution for each screen size to obtain the optimum picture
 quality due to the nature of the panel. Therefore, a resolution other than the specified resolution
 may degrade the picture quality. To avoid this, it is recommended that you select the optimum
 resolution specified for the screen size of your product.
- Check the frequency when you exchange a CDT monitor (connected to a PC) for an LCD monitor.
 If the LCD monitor does not support 85Hz, change the vertical frequency to 60Hz using the CDT monitor before you exchange it with the LCD monitor.

If a signal that belongs to the following standard signal modes is transmitted from your PC, the screen will automatically be adjusted. If the signal transmitted from the PC does not belong to the standard signal modes, the screen may be blank even though the power LED turns on. In such a case, change the settings according to the following table by referring to the graphics card user manual.

| Resolution | Horizontal Frequency (kHz) | Vertical Frequency (Hz) | Pixel Clock (MHz) | Sync Polarity (H/V) |
|-----------------------|----------------------------------|-------------------------------|----------------------|------------------------|
| IBM, 720 x 400 | 31.469 | 70.087 | 28.322 | -/+ |
| MAC, 640 x 480 | 35.000 | 66.667 | 30.240 | -/- |
| MAC, 832 x 624 | 49.726 | 74.551 | 57.284 | -/- |
| MAC, 1152 x 870 | 68.681 | 75.062 | 100.000 | -/- |
| VESA, 640 x 480 | 31.469 | 59.940 | 25.175 | -/- |
| VESA, 640 x 480 | 37.861 | 72.809 | 31.500 | -/- |
| VESA, 640 x 480 | 37.500 | 75.000 | 31.500 | -/- |
| VESA, 800 x 600 | 35.156 | 56.250 | 36.000 | +/+ |
| VESA, 800 x 600 | 37.879 | 60.317 | 40.000 | +/+ |
| VESA, 800 x 600 | 48.077 | 72.188 | 50.000 | +/+ |
| VESA, 800 x 600 | 46.875 | 75.000 | 49.500 | +/+ |
| VESA, 1024 x 768 | 48.363 | 60.004 | 65.000 | -/- |
| VESA, 1024 x 768 | 56.476 | 70.069 | 75.000 | -/- |
| VESA, 1024 x 768 | 60.023 | 75.029 | 78.750 | +/+ |
| VESA, 1152 x 864 | 67.500 | 75.000 | 108.000 | +/+ |
| VESA, 1280 x 720 | 45.000 | 60.000 | 74.250 | +/+ |
| VESA, 1280 x 800 | 49.702 | 59.810 | 83.500 | -/+ |
| VESA, 1280 x 1024 | 63.981 | 60.020 | 108.000 | +/+ |
| VESA, 1280 x 1024 | 79.976 | 75.025 | 135.000 | +/+ |
| VESA, 1440 x 900 | 55.935 | 59.887 | 106.500 | -/+ |
| VESA, 1600 x 900 (RB) | 60.000 | 60.000 | 108.000 | +/+ |
| VESA, 1680 x 1050 | 65.290 | 59.954 | 146.250 | -/+ |
| VESA, 1920 x 1080p | 67.500 | 60.000 | 148.500 | +/+ |



Horizontal Frequency

The time required to scan a single line from the left to the right side of the screen is called a horizontal cycle. The reciprocal number of a horizontal cycle is called horizontal frequency. Horizontal frequency is measured in kHz.

Vertical Frequency

Repeating the same picture dozens of times per second allows you to view natural pictures. The repeat frequency is called "vertical frequency" or "refresh rate" and is indicated in Hz.

Contact SAMSUNG WORLD WIDE



If you have any questions or comments relating to Samsung products, please contact the SAMSUNG customer care center.

| NORTH AMERICA | | | |
|---------------|---------------------------|--|--|
| U.S.A | 1-800-SAMSUNG (726-7864) | http://www.samsung.com | |
| CANADA | 1-800-SAMSUNG (726-7864) | http://www.samsung.com/ca (English) http://www.samsung.com/ca_fr (French) | |
| MEXICO | 01-800-SAMSUNG (726-7864) | http://www.samsung.com | |

| LATIN AMERICA | | | | |
|---------------|--|--|--|--|
| ARGENTINE | 0800-333-3733 | http://www.samsung.com | | |
| BOLIVIA | 800-10-7260 | http://www.samsung.com | | |
| BRAZIL | 0800-124-421 4004-0000 | http://www.samsung.com | | |
| CHILE | 800-SAMSUNG (726-7864) From mobile 02-24 82 82 00 | http://www.samsung.com/cl | | |
| COLOMBIA | 01-8000 112 112 Bogotá: 6001272 | http://www.samsung.com/co | | |
| COSTA RICA | 0-800-507-7267 | http://www.samsung.com/latin (Spanish) | | |
| | | http://www.samsung.com/latin_en (English) | | |
| DOMINICA | 1-800-751-2676 | http://www.samsung.com/latin (Spanish) | | |
| | | http://www.samsung.com/latin_en (English) | | |
| ECUADOR | 1-800-10-7267 | http://www.samsung.com/latin (Spanish) | | |
| | | http://www.samsung.com/latin_en (English) | | |
| EL SALVADOR | 800-6225 | http://www.samsung.com/latin (Spanish) | | |
| | | http://www.samsung.com/latin_en (English) | | |

| LATIN AMERICA | | |
|-------------------|-----------------------------------|--|
| GUATEMALA | 1-800-299-0013 | http://www.samsung.com/latin (Spanish) |
| | | http://www.samsung.com/latin_en (English) |
| HONDURAS | 800-27919267 | http://www.samsung.com/latin (Spanish) |
| | | http://www.samsung.com/latin_en (English) |
| JAMAICA | 1-800-234-7267 | http://www.samsung.com |
| NICARAGUA | 00-1800-5077267 | http://www.samsung.com/latin (Spanish) |
| | | http://www.samsung.com/latin_en (English) |
| PANAMA | 800-7267 | http://www.samsung.com/latin (Spanish) |
| | | http://www.samsung.com/latin_en (English) |
| PARAGUAY | 009-800-542-0001 | http://www.samsung.com |
| PERU | 0-800-777-08 (Only from landline) | http://www.samsung.com |
| | 336-8686 (From HHP & landline) | |
| PUERTO RICO | 1-800-682-3180 | http://www.samsung.com |
| TRINIDAD & TOBAGO | 1-800-SAMSUNG (726-7864) | http://www.samsung.com |
| URUGUAY | 000-405-437-33 | http://www.samsung.com |
| VENEZUELA | 0-800-100-5303 | http://www.samsung.com |

| EUROPE | | |
|----------|---|---|
| AUSTRIA | 0810 - SAMSUNG (7267864, € 0.07/min) | http://www.samsung.com |
| BELGIUM | 02-201-24-18 | http://www.samsung.com/be (Dutch) http://www.samsung.com/be_fr (French) |
| BOSNIA | 051 133 1999 | http://www.samsung.com |
| BULGARIA | 07001 33 11 , normal tariff | http://www.samsung.com |
| CROATIA | 062 SAMSUNG (062 726 786) | http://www.samsung.com |

| EUROPE | | | |
|-------------|--|--|--|
| CYPRUS | 8009 4000 only from landline | http://www.samsung.com | |
| | (+30) 210 6897691 from mobile and land line | | |
| CZECH | 800 - SAMSUNG (800-726786) | http://www.samsung.com | |
| | Oasis Florenc, Sokolovská 394/17, till 8.2.2013 . From 8.2.2013: Sams | Samsung Electronics Czech and Slovak, s.r.o., Oasis Florenc, Sokolovská 394/17, 180 00, Praha 8 till 8.2.2013 . From 8.2.2013: Samsung Electronics Czech and Slovak, s.r.o. V Parku 2343/24, 148 00 - Praha 4 | |
| DENMARK | 70 70 19 70 | http://www.samsung.com | |
| EIRE | 0818 717100 | http://www.samsung.com | |
| ESTONIA | 800-7267 | http://www.samsung.com/ee | |
| FINLAND | 030-6227 515 | http://www.samsung.com | |
| FRANCE | 01 48 63 00 00 | http://www.samsung.com/fr | |
| GERMANY | 0180 5 SAMSUNG bzw. 0180 5 7267864* (*0,14 €/Min. aus dem dt. Festnetz, aus dem Mobilfunk max. 0,42 €/Min.) | http://www.samsung.com | |
| GREECE | 80111-SAMSUNG (80111 726 7864) only from land line (+30) 210 6897691 from mobile and land line | http://www.samsung.com | |
| HUNGARY | 06-80-SAMSUNG (726-7864) | http://www.samsung.com | |
| ITALIA | 800-SAMSUNG (726-7864) | http://www.samsung.com | |
| LATVIA | 8000-7267 | http://www.samsung.com/lv | |
| LITHUANIA | 8-800-77777 | http://www.samsung.com/lt | |
| LUXEMBURG | 261 03 710 | http://www.samsung.com | |
| MONTENEGRO | 020 405 888 | http://www.samsung.com | |
| NETHERLANDS | 0900 - SAMSUNG (0900-7267864) (€ 0,10/Min) | http://www.samsung.com | |
| NORWAY | 815 56480 | http://www.samsung.com | |
| POLAND | 0 801-1SAMSUNG(172-678) * lub +48 22 607-93-33 ** * (całkowity koszt połączenia jak za 1 impuls według taryfy operatora) ** (koszt połączenia według taryfy operatora) | http://www.samsung.com/pl | |

| EUROPE | | |
|-------------|---|---|
| PORTUGAL | 808 20 - SAMSUNG (808 20 7267) | http://www.samsung.com |
| ROMANIA | 08008 SAMSUNG (08008 726 7864) TOLL FREE No. | http://www.samsung.com |
| SERBIA | +381 11 321 6899 (old number still active 0700 7267864) | http://www.samsung.com |
| SLOVAKIA | 0800 - SAMSUNG (0800-726 786) | http://www.samsung.com |
| SPAIN | 902 - 1 - SAMSUNG (902 172 678) | http://www.samsung.com |
| SWEDEN | 0771 726 7864 (SAMSUNG) | http://www.samsung.com |
| SWITZERLAND | 0848-SAMSUNG (7267864, CHF 0.08/min) | http://www.samsung.com/ch (German) http://www.samsung.com/ch_fr (French) |
| U.K | 0330 SAMSUNG (7267864) | http://www.samsung.com |

| CIS | | |
|-------------|------------------------------------|---|
| ARMENIA | 0-800-05-555 | http://www.samsung.com |
| AZERBAIJAN | 088-55-55-555 | http://www.samsung.com |
| BELARUS | 810-800-500-55-500 | http://www.samsung.com |
| GEORGIA | 0-800-555-555 | http://www.samsung.com |
| KAZAKHSTAN | 8-10-800-500-55-500 (GSM: 7799) | http://www.samsung.com |
| KYRGYZSTAN | 00-800-500-55-500 | http://www.samsung.com |
| MOLDOVA | 0-800-614-40 | http://www.samsung.com |
| MONGOLIA | +7-800-555-55-55 | http://www.samsung.com |
| RUSSIA | 8-800-555-55-55 | http://www.samsung.com |
| TADJIKISTAN | 8-10-800-500-55-500 | http://www.samsung.com |
| UKRAINE | 0-800-502-000 | http://www.samsung.com/ua (Ukrainian) http://www.samsung.com/ua_ru (Russian) |
| UZBEKISTAN | 8-10-800-500-55-500 | http://www.samsung.com |

| ASIA PACIFIC | | |
|--------------|---|--|
| AUSTRALIA | 1300 362 603 | http://www.samsung.com |
| CHINA | 400-810-5858 | http://www.samsung.com |
| HONG KONG | (852) 3698 - 4698 | http://www.samsung.com/hk (Chinese) |
| | | http://www.samsung.com/hk_en (English) |
| INDIA | 1800 3000 8282 1800 266 8282 | http://www.samsung.com/in |
| INDONESIA | 0800-112-8888 021-5699-7777 | http://www.samsung.com/id |
| JAPAN | 0120-327-527 | http://www.samsung.com |
| MALAYSIA | 1800-88-9999 | http://www.samsung.com/my |
| NEW ZEALAND | 0800 SAMSUNG (0800 726 786) | http://www.samsung.com |
| PHILIPPINES | 1-800-10-SAMSUNG (726-7864) for PLDT | http://www.samsung.com/ph |
| | 1-800-3-SAMSUNG (726-7864) for Digitel | |
| | 1-800-8-SAMSUNG (726-7864) for Globe | |
| | 02-5805777 | |
| SINGAPORE | 1800-SAMSUNG (726-7864) | http://www.samsung.com |
| TAIWAN | 0800-329-999 | http://www.samsung.com |
| | 0266-026-066 | |
| THAILAND | 1800-29-3232 | http://www.samsung.com/th |
| | 02-689-3232 | |
| VIETNAM | 1 800 588 889 | http://www.samsung.com |

| MENA | | |
|---------|--------------|--|
| BAHRAIN | 8000-4726 | http://www.samsung.com/ae (English) |
| | | http://www.samsung.com/ae_ar (Arabic) |
| EGYPT | 08000-726786 | http://www.samsung.com |
| IRAN | 021-8255 | http://www.samsung.com |
| JORDAN | 800-22273 | http://www.samsung.com/Levant |
| | 065777444 | (English) |

| MENA | | |
|--------------|------------------------|--|
| KUWAIT | 183-2255 (183-CALL) | http://www.samsung.com/ae (English) http://www.samsung.com/ae_ar (Arabic) |
| MOROCCO | 080 100 2255 | http://www.samsung.com |
| OMAN | 800-SAMSUNG (726-7864) | http://www.samsung.com/ae (English) http://www.samsung.com/ae_ar |
| | 000 0055 (000 0444) | (Arabic) |
| QATAR | 800-2255 (800-CALL) | http://www.samsung.com/ae (English) http://www.samsung.com/ae_ar |
| | | (Arabic) |
| SAUDI ARABIA | 9200-21230 | http://www.samsung.com/sa (Arabic) |
| SYRIA | 18252273 | http://www.samsung.com/Levant (English) |
| TURKEY | 444 77 11 | http://www.samsung.com |
| U.A.E | 800-SAMSUNG (726-7864) | http://www.samsung.com |

| AFRICA | | |
|----------------|-------------------------|------------------------|
| ANGOLA | 91-726-7864 | http://www.samsung.com |
| BOTSWANA | 0800-726-000 | http://www.samsung.com |
| CAMEROON | 7095- 0077 | http://www.samsung.com |
| COTE D' IVOIRE | 8000 0077 | http://www.samsung.com |
| GHANA | 0800-10077 | http://www.samsung.com |
| | 0302-200077 | |
| KENYA | 0800 545 545 | http://www.samsung.com |
| NAMIBIA | 8197267864 | http://www.samsung.com |
| NIGERIA | 0800-726-7864 | http://www.samsung.com |
| SENEGAL | 800-00-0077 | http://www.samsung.com |
| SOUTH AFRICA | 0860-SAMSUNG (726-7864) | http://www.samsung.com |
| TANZANIA | 0685 88 99 00 | http://www.samsung.com |
| UGANDA | 0800 300 300 | http://www.samsung.com |
| ZAMBIA | 211350370 | http://www.samsung.com |

Responsibility for the Pay Service (Cost to Customers)



When the service is requested, in spite of in warranty, we may charge you for a visit from a service technician in the following cases.

Not a product defect

Cleaning of the product, Adjustment, Explanation, Re-installation and etc.

- If a service technician gives instructions on how to use product or simply adjusts options without disassembling product.
- If a defect is caused by external environmental factors. (Internet, Antenna, Wired Signal, etc.)
- If a product is reinstalled or devices are connected additionally after installing the purchased product for the first time.
- If a product is reinstalled to move to a different spot or to move to a different house.
- If customer requests instructions on how to use because of another company's product.
- If customer requests instructions on how to use the network or another company's program.
- If customer requests software installation and setup for the product.
- If a service technician removes/cleans dusts or foreign materials inside of the product.
- If customer requests an installation additionally after purchasing a product through home-shopping or online.

A Product damage caused by customer's fault

Product damage caused by customer's mishandling or wrong repair

If a product damage is caused by;

- external impact or drop.
- use of supplies or separately sold product unspecified by Samsung.
- repair from a person besides an engineer of outsourcing service company or partner of Samsung Electronics Co., Ltd.
- remodeling or repairing the product by customer.
- using it with incorrect voltage or non-authorised electrical connections.
- not following the "cautions" in User Manual.

Others

- If product fails by natural disaster. (lightning, fire, earthquake, flood damage, etc)
- If consumable components are all used up. (Battery, Toner, Fluorescent lights, Head, Vibrator, Lamp, Filter, Ribbon, etc.)



If customer requests a service in case the product has no defect, service fee may be charged. So please read User Manual first.

Correct Disposal

Correct Disposal of This Product (Waste Electrical & Electronic Equipment)



(Applicable in countries with separate collection systems)

This marking on the product, accessories or literature indicates that the product and its electronic accessories (e.g. charger, headset, USB cable) should not be disposed of with other household waste at the end of their working life. To prevent possible harm to the environment or human health from uncontrolled waste disposal, please separate these items from other types of waste and recycle them responsibly to promote the sustainable reuse of material resources.

Household users should contact either the retailer where they purchased this product, or their local government office, for details of where and how they can take these items for environmentally safe recycling.

Business users should contact their supplier and check the terms and conditions of the purchase contract. This product and its electronic accessories should not be mixed with other commercial wastes for disposal.

Terminology

OSD (On Screen Display)

On screen display (OSD) allows you to customize on-screen settings to optimize the picture quality as required. You can change the screen brightness, tint, size and many other settings using menus displayed on the screen.

Gamma

The Gamma menu adjusts the grey scale that represents middle tones on the screen. Adjusting the brightness brightness the whole screen, but adjusting Gamma only brightness the medium brightness.

Grey scale

Scale refers to levels of color intensity that show variations of color change from darker areas to brighter areas on the screen. Changes to the screen brightness are expressed with black and white variation, and grey scale refers to the medium area between black and white. Changing the grey scale through Gamma adjustment will change the medium brightness on the screen.

Scanning rate

Scanning rate, or refresh rate, refers to the frequency of screen refreshes. Screen data is transmitted as it refreshes to display an image, although the refreshing is invisible to the naked eye. The number of screen refreshes is called scanning rate and is measured in Hz. A scanning rate of 60Hz means that the screen refreshes 60 times per second. The screen scanning rate depends on the performance of the graphics cards in your PC and monitor.

Horizontal Frequency

Characters or images displayed on the monitor screen consist of numerous dots (pixels). Pixels are transmitted in horizontal lines, which are then arranged vertically to create an image. The horizontal frequency is measured in kHz and represents how many times horizontal lines per second are transmitted and displayed on the monitor screen. A horizontal frequency of 85 means that the horizontal lines that make up an image are transmitted 85000 times per second. The horizontal frequency is indicated in 85kHz.

Vertical Frequency

One image is made of numerous horizontal lines. The vertical frequency is measured in Hz and represents how many images can be created per second by those horizontal lines. A vertical frequency of 60 means that an image is transmitted 60 times per second. The vertical frequency is also called "refresh rate" and affects screen flicker.

Resolution

Resolution is the number of horizontal pixels and vertical pixels that form a screen. It represents the level of display detail.

A higher resolution displays a greater amount of information on the screen and is suitable for performing multiple tasks at the same time.

E.g. A resolution of 1366 x 768 consists of 1366 horizontal pixels (horizontal resolution) and 768 vertical lines (vertical resolution).

E.g. A resolution of 1920 x 1080 consists of 1920 horizontal pixels (horizontal resolution) and 1080 vertical lines (vertical resolution).

Plug & Play

The Plug & Play feature allows the automatic exchange of information between a monitor and PC to produce an optimum display environment.

The monitor uses VESA DDC (international standard) to execute Plug & Play.

Index

В

| Before Connecting 28 | Image Size 45 |
|---------------------------------------|---|
| Blue 52 | INFORMATION 67 |
| Brightness 38 | Installation 24 |
| С | K |
| Checking the Contents 19 | Key Repeat Time 64 |
| Coarse 48 | |
| Color Tone 53 | L |
| Connecting and Using a PC 29 | Language 55 |
| Contact SAMSUNG WORLD WIDE 82 | Language 33 |
| Contrast 39 | |
| Copyright 7 | M |
| Correct Disposal 90 | MagicTune 69 |
| Correct posture to use the product 18 | MultiScreen 71 |
| Customized Key 66 | |
| | 0 |
| D | Off Timer 61 |
| Display Time 57 | |
| Display Time 37 | Р |
| | Parts 21 |
| E | PC/AV Mode 63 |
| Eco Saving 60 | FG/AV Widde 63 |
| - | Q |
| F | Q & A 76 |
| Fine 49 | |
| G | R |
| Gamma 54 | Red 50 |
| General 78 | Requirements Before Contacting Samsung Customer Service Center 73 |
| Green 51 | Reset 59 |
| | Responsibility for the Pay Service (Cost to |
| H | Customers) 88 |
| HDMI Black Level 46 | |

Index

S

Safety Precautions 10

SAMSUNG MAGIC Angle 43

SAMSUNG MAGIC Bright 41

SAMSUNG MAGIC Upscale 44

Sharpness 40

Source Detection 65

Standard Signal Mode Table 80

Т

Terminology 91

Transparency 58

Turn Off After 62